



HIGHLIGHTS

- Excellent anti-resoiling properties
- Safe on stain-resistant (fifth generation) carpets
- Excellent extraction and bonnet cleaner
- Leaves a pleasant fresh scent

TYPICAL PROPERTIES

Specific Gravity: 1.045

pH: 8.0

Phosphates (P₂O₅): <1%

Solids: 15.0%

Solvents: 4.0%

Appearance: Clear light blue liquid

Fragrance:

Fresh

DILUTION RATIOS

Low: 1:32

High: 1:256

CARPET EXTRACTION/ SPOTTER

Formulated for today's
Stain resistant carpets

- Steam extraction cleaning, Bonnet cleaning, Traffic lane pre-spotting
- Formulated with synthetic wetting agents, grease emulsifiers, watersofteners and optical brighteners

A concentrated low foaming steam extraction and bonnet cleaner that works effectively on all types of carpets, including the latest generation of stain resistant carpets. Formulated with synthetic wetting agents, grease emulsifiers, water softeners and optical brighteners. Leaves a nice fresh scent. Excellent anti-resoiling properties keep carpet clean longer than conventional extraction products.

DIRECTIONS FOR USE

Remove cap. With handle facing left, insert into cabinet until it locks into place. Press button to start flow of solution; release button to stop flow of solution.

To lock the high flow button in the ON position: Press button until it locks into place.

To unlock, press release button on left side of pump.

To remove concentrate, place hand under container, slide release lever to the right and pull concentrate container out.

For steam extraction add solution directly to tank. Pre-spray heavily soiled or traffic lane areas. Spray approximately 100 sq. ft. at a time, holding sprayer 12" to 16" above carpet. Avoid soaking carpet. Dampen bonnet pad with water, do not soak. Spray bonnet with cleaning solution and place bonnet under machine on carpet, sprayed-side down. Buff carpet over sprayed area, turning the pad over or changing it when heavily soiled. Allow carpet to dry for 30 minutes to an hour then vacuum thoroughly. NOTE -if furniture must be replaced before carpet is dried, place cardboard strips under furniture legs.

6475DC_0807

Manufactured by:
ABC COMPOUNDING COMPANY, INC.
ATLANTA, GA / DALLAS, TX

